



- C1: DELTA = 14°37'02"
RADIUS = 546.39
LENGTH = 139.39
- C2: DELTA = 32°02'34"
RADIUS = 120.77
LENGTH = 87.55
- C3: DELTA = 25°19'57"
RADIUS = 1480.29
LENGTH = 654.484
- L1: S 89°37'17"E
7.32
- L2: S 67°31'09"E
428.87

**SURVEY IN SECTIONS 5, 6 & 7,
TOWNSHIP 35 NORTH,
RANGE 8 EAST, W.M.**

SCALE 1 INCH = 600 FEET
BASIS OF BEARINGS = MAGNETIC
(VARIATION = 22 1/2° EAST)



<p>AUDITOR'S CERTIFICATE</p> <p>FILED FOR RECORD THIS 13... DAY OF October... 1988 AT 3:40 P.M. IN BOOK 8 OF RECORDS... AT PAGE 777 AT THE REQUEST OF DENNIS M. DEMILIO.</p> <p><i>Jerry McIntyre</i> COUNTY AUDITOR</p> <p><i>Michael Reed</i> DEPUTY AUDITOR</p>	<p>SURVEYOR'S CERTIFICATE</p> <p>THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF THE SURVEY RECORDING ACT AT THE REQUEST OF GEORGIA-PACIFIC CORPORATION IN... Spring 1985</p> <p><i>Dennis M. Demilio</i> CERTIFICATE NO. 01493</p>	<p>PORTIONS OF SECTIONS 5, 6 & 7, TOWNSHIP 35 NORTH, RANGE 8 EAST, W.M.</p> <p>SKAGIT COUNTY, WASHINGTON</p>	<p>RECORD OF SURVEY</p> <p>FOR GEORGIA-PACIFIC CORPORATION P.O. BOX 1236, BELLINGHAM, WASHINGTON</p> <table border="1"> <tr> <td>Drawn By: DJM</td> <td>Date: 08/09/88</td> <td>Job:</td> </tr> <tr> <td>Checked By: DMD</td> <td>Scale: 1" = 600'</td> <td>Sheet: 1 OF 2</td> </tr> </table>	Drawn By: DJM	Date: 08/09/88	Job:	Checked By: DMD	Scale: 1" = 600'	Sheet: 1 OF 2
Drawn By: DJM	Date: 08/09/88	Job:							
Checked By: DMD	Scale: 1" = 600'	Sheet: 1 OF 2							

SURVEY IN SECTIONS 5, 6 AND 7, TOWNSHIP 35 NORTH, RANGE 8 EAST, W.M.

LEGAL DESCRIPTION:

THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 5; THE SOUTHWEST 1/4 OF SECTION 6; THAT PART OF NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 7 LYING NORTH OF THE GREAT NORTHERN RAILWAY COMPANY RIGHT-OF-WAY; ALL IN TOWNSHIP 35 NORTH, RANGE 8 EAST, W.M., EXCLUDED FROM THE ABOVE DESCRIBED PROPERTY ALL COUNTY ROADS AND RIGHTS-OF-WAY.

SUBJECT TO AN EASEMENT FOR ELECTRIC TRANSMISSION LINE AS DESCRIBED UNDER AUDITOR FILE NUMBER 183097.

ALSO SUBJECT TO ROAD RIGHTS-OF-WAY AS DESCRIBED UNDER AUDITOR FILE NUMBERS 127138 AND 127139.

ALL AS DESCRIBED AND RECORDED UNDER AUDITOR FILE NUMBER 418074, RECORDS OF SNOHOMISH COUNTY, WASHINGTON.



SURVEYOR'S NOTES:

- 1.) "□" DENOTES GENERAL LAND OFFICE CORNER FOUND, COMPUTED OR SET BY THIS SURVEY. (SEE CORNER DESCRIPTIONS)
- 2.) "□" DENOTES 5/8" REBAR AND PLASTIC CAP MARKED "D.M. DORNIER L.S. 21423", SET FOR PROPERTY CORNERS.
- 3.) FOR MORE INFORMATION ON THE GENERAL LAND OFFICE CORNERS USED OR RE-ESTABLISHED BY THIS SURVEY, REFER TO LAND CORNER RECORDS FILED WITH THE SNOHOMISH COUNTY AUDITOR'S OFFICE.
- 4.) PORTIONS OF THE NORTHEAST 1/4 OF SECTION 7 WERE COMPUTED AS PER RECORD OF SURVEY FILED UNDER AUDITOR FILE NUMBER 88208, RECORDS OF SNOHOMISH COUNTY, WASHINGTON.

CORNER DESCRIPTIONS:

- 1.) NORTHWEST CORNER SECTION 5. FOUND 3/4" REBAR AND ALUMINUM CAP AS PER SURVEY FILED IN VOLUME 5 OF SURVEYS, PAGE 252, RECORDS OF SNOHOMISH COUNTY, WASHINGTON. HELD FOR SECTION CORNER.
- 2.) NORTH 1/4 CORNER SECTION 5. NOT FOUND. SET 5/8" X 30" REBAR WITH ALUMINUM CAP MARKED "LS 21423" INSIDE 2" IRON PIPE AT THE COMPUTED LOCATION USING 1838 FIELD NOTES FROM H.J. STEEN AND J.W. STEEN ON FILE AT THE SCOTT PAPER TIMBER OFFICE, HAMILTON, WASHINGTON.
- 3.) NORTHEAST CORNER SECTION 5. NOT FOUND. SET 5/8" X 30" REBAR WITH ALUMINUM CAP MARKED "LS 21423" INSIDE 2" IRON PIPE AT THE COMPUTED LOCATION USING 1838 FIELD NOTES FROM H.J. STEEN AND J.W. STEEN ON FILE AT THE SCOTT PAPER TIMBER OFFICE, HAMILTON, WASHINGTON.
- 4.) NORTH 1/4 CORNER SECTION 6. NOT FOUND AND NOT FOUND IN 1838 BY STEEN. SET 5/8" X 30" REBAR WITH ALUMINUM CAP MARKED "LS 21423" INSIDE 2" IRON PIPE IN MOUND OF ROCKS AT THE COMPUTED SINGLE PROPORTION LOCATION.
- 5.) NORTHEAST CORNER SECTION 6. FOUND 3/4" IRON PIPE 5" ABOVE GROUND AND 3 DEARTH TREE STUMPS AND VISIBLE SCRUBS. HELD FOR SECTION CORNER.
- 6.) WEST 1/4 CORNER SECTION 6. FOUND 1" IRON PIPE WITH ONE BRASS CAP AS PER SURVEY FILED IN VOLUME 5 OF SURVEYS, AT PAGE 252, RECORDS OF SNOHOMISH COUNTY, WASHINGTON. HELD FOR 1/4 CORNER.
- 7.) CENTER OF SECTION 6. SET 5/8" X 30" REBAR WITH ALUMINUM CAP MARKED "LS 21423" INSIDE 2" IRON PIPE AT THE COMPUTED LOCATION FOR SECTION CENTER.
- 8.) EAST 1/4 CORNER SECTION 6. NOT FOUND. SET 5/8" X 30" REBAR WITH ALUMINUM CAP MARKED "LS 21423" INSIDE 2" IRON PIPE AT THE COMPUTED SINGLE PROPORTION LOCATION.
- 9.) EAST 1/4 CORNER SECTION 5. NOT FOUND. SET 5/8" X 30" REBAR WITH ALUMINUM CAP MARKED "LS 21423" INSIDE 2" IRON PIPE AT THE COMPUTED SINGLE PROPORTION LOCATION.
- 10.) SOUTH 1/4 CORNER SECTION 6. FOUND CONCRETE MONUMENT. HELD FOR SECTION CORNER.
- 11.) SOUTHEAST CORNER SECTION 6. FOUND 1" IRON PIPE AND 3 REFERENCES. HELD FOR SECTION CORNER.
- 12.) SOUTH 1/4 CORNER SECTION 5. FOUND 5/8" IRON PIN 2" ABOVE GROUND. HELD FOR 1/4 CORNER.
- 13.) SOUTHWEST CORNER SECTION 5. FOUND 3/4" IRON PIPE WITH PLASTIC CAP (LS MARKER ILLUSTABLE), AND 1 REFERENCE. HELD FOR SECTION CORNER.
- 14.) EAST 1/4 CORNER SECTION 7 AS PER SURVEY FILED IN VOLUME 5 OF SURVEYS, AT PAGE 187, RECORDS OF SNOHOMISH COUNTY, WASHINGTON.